

## ONE PIECE PILOT LIGHTS

Complete Pilot Light With Integrated LED

L20SC20H

LED One Piece Pilotlight 230V ac/dc Green



- IP66 / IP69K
- 12-24V, 115V, 230V ac/dc
- Compact 37.2 mm behind panel depth
- Long lifetime up to 100,000 hours

### PRODUCT DESCRIPTION

LED pilot lights in a robust housing with modern design that are easy to install in a 22.5mm hole.

The one piece body has an integrated LED and easily accessible screw connections at the bottom of the base.

The unit is ideal for harsh industrial environments thanks to a high impact resistance and protection class rating of IP66 / IP69K and therefore suitable for a wide range of applications.

### SPECIFICATIONS

<b>Approvals</b>	BV, CB, CCC, CE, REACH, RoHS, UL
<b>Climate resistance cyclic damp heat</b>	IEC 60068-2-3
<b>Color</b>	Green
<b>Connection</b>	Screw
<b>Frequenze</b>	50/60 Hz
<b>Impact resistance</b>	IK05
<b>LED supply voltage</b>	230V ac/dc
<b>LED Voltage Tolerance</b>	±10%
<b>Lifetime at rated supply voltage (25°C)</b>	50000 h
<b>Power consumption</b>	4.6 mA
<b>Protection Class</b>	II
<b>Protection rating front of panel</b>	IP69, IP69K, NEMA Type 4X, NEMA Type 12, NEMA Type 13
<b>Protection rating rear of panel</b>	IP20
<b>Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3)</b>	4 kV
<b>Rated insulation voltage Ui</b>	300 V
<b>Structural Depth</b>	37.2 mm
<b>Temperature range bearing, from</b>	-40 °C

Temperature range bearing, to	70 °C
-------------------------------	-------

Temperature range from	-25 °C
------------------------	--------

Temperature range to	70 °C
----------------------	-------

Weight	19 g
--------	------

Width	30 mm
-------	-------

