

## MINI CAM SWITCH 10 A

223501

"MINI CAM SWITCH 1 POLE ""0-1"" A4"

- Compact size
- Switching current 10 A
- Mounting Ø 22.5mm or Ø 16mm
- IP65



### PRODUCT DESCRIPTION

Miniature cam switches rated at 10A in a compact size ideal for applications with limited available space.

The mounting is simple with only a single hole required in either Ø16 mm or Ø22 mm.

The terminal screws are mounted at a 45° angle making electrical connection easier if the switch has already been mounted.

Each switch is supplied complete with engraved legend plate, frame and handle.

### SPECIFICATIONS

Angle	90°
Cable area max	2x1,5 mm <sup>2</sup>
Cable area min	1x0,5 mm <sup>2</sup>
Conventional free air thermal current I <sub>th</sub>	10 A
Function	Stable
Mounting	Single hole mounting Ø16 mm / Ø22,5 mm
Number Of Contacts	1
Number of poles	1
Number of positions	2
Plate	30x30
Protection rating front of panel	IP65
Protection rating rear of panel	IP20

Rated insulation voltage Ui	500 V
Rated operating current Ie (AC15/230V)	2.5 A
Rated operating current Ie (AC21A/22A)	10 A
Rated operating current Ie (DC-1/24 VDC)	10 A
Rated operating power (AC23A/3x230V)	1.8 kW
Rated operating power (AC23A/3x400V)	3 kW
Rated operating power (AC3/3x230V)	1.8 kW
Rated operating power (AC3/3x400V)	2.2 kW
Standards	CE, CSA 22.2, IEC 60947-3, IEC 60947-1, UL, UL 508
Temperature range from	-20 °C
Temperature range to	50 °C
Type/Model	ON-OFF switch
Weight	32 g

