C5 INDUSTRIAL RELAY

3-pole 16 A

C5-A3024A
Relay 11 Pin 3 Pole 16A 24V ac



- Marking system
- Colour-coded test button, both lockable and non-lockable
- Mechanical indication, double windows

PRODUCT DESCRIPTION

SPECIFICATIONS

Working Un	0,80-1,10
Nominal power ac	2.4 VA
Coil Voltage AC	24 V AC

Number Of Contacts	3
Contact Material	AgNi
Nominal current	16 A
Switching Capability Voltage	400 V
Breaking Capacity Current	16 A
The Recommended Maximum Load	16 A/400 V AC-1; 0,5 A/110 V DC-1
Resistive Load 110 V DC Max	55 W
Resistive Load 24 V dc Max	360 W
Surge Current (20Ms)	40 A
Bounce Time	3
Release Time Kontaktstudstid	11 ms

IP Class	IP40
Isolation Contact / Contact	4000 V
Isolation Contact / Coil	4000 V
Insulation Class EN60947	500 V, Pullution 3, Group C

Temperature range from	-40 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	80 °C
Temperature range to	60 °C
Frequency	50 Hz
Weight	95 g
Approvals	CE, UL, RoHS, CSA, Gost R







