

## C5 INDUSTRIAL RELAY

3-pole 16 A

C5-A3024A

Relay 11 Pin 3 Pole 16A 24V ac

- Marking system
- Colour-coded test button, both lockable and non-lockable
- Mechanical indication, double windows



### PRODUCT DESCRIPTION

## SPECIFICATIONS

<b>Working Un</b>	0,80-1,10
<b>Nominal power ac</b>	2.4 VA
<b>Coil Voltage AC</b>	24 V AC
<b>Number Of Contacts</b>	3
<b>Contact Material</b>	AgNi
<b>Nominal current</b>	16 A
<b>Switching Capability Voltage</b>	400 V
<b>Breaking Capacity Current</b>	16 A
<b>The Recommended Maximum Load</b>	16 A/400 V AC-1; 0,5 A/110 V DC-1
<b>Resistive Load 110 V DC Max</b>	55 W
<b>Resistive Load 24 V dc Max</b>	360 W
<b>Surge Current (20Ms)</b>	40 A
<b>Bounce Time</b>	3
<b>Release Time Kontaktstudstid</b>	11 ms
<b>IP Class</b>	IP40
<b>Isolation Contact / Contact</b>	4000 V
<b>Isolation Contact / Coil</b>	4000 V
<b>Insulation Class EN60947</b>	500 V, Pollution 3, Group C

Temperature range from	-40 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	80 °C
Temperature range to	60 °C
Frequency	50 Hz
Weight	95 g
Approvals	CE, UL, RoHS, CSA, Gost R

