

C5 INDUSTRIAL RELAY

3-pole 16 A

C5-X1048D

Relay 11 Pin 1 Pole 16A N/O 3mm GAP 48V dc

- Marking system
- Colour-coded test button, both lockable and non-lockable
- Mechanical indication, double windows



PRODUCT DESCRIPTION

SPECIFICATIONS

Working Un	0,80-1,10
Nominal power dc	1.3 W
Coil Voltage DC	48 V DC
Number Of Contacts	1
Contact Material	AgNi
Nominal current	16 A
Switching Capability Voltage	400 V
Breaking Capacity Current	16 A
The Recommended Maximum Load	16 A/400 V AC-1; 7 A/110 V DC-1
Resistive Load 110 V DC Max	770 W
Resistive Load 24 V dc Max	360 W
Surge Current (20Ms)	40 A
Bounce Time	3
Release Time Kontaktstuds tid	11 ms
IP Class	IP40
Isolation Contact / Contact	4000 V
Isolation Contact / Coil	4000 V

Insulation Class EN60947

500 V, Pollution 3, Group C

Temperature range from

-40 °C

Temperature range bearing, from

-40 °C

Temperature range bearing, to

80 °C

Temperature range to

60 °C

Frequency

50 Hz

Weight

90 g

Approvals

RoHS

