

C5 INDUSTRIAL RELAY

3-pole 16 A

C5-M10DX24D

Relay 4 Pin 1 Pole 16A N/O Mag Diode LED 24V dc

- Marking system
- Colour-coded test button, both lockable and non-lockable
- Mechanical indication, double windows



PRODUCT DESCRIPTION

SPECIFICATIONS

Working Un	0,80-1,10
Nominal power dc	1.3 W
Coil Voltage DC	24 V DC
Number Of Contacts	1
Contact Material	AgNi
Nominal current	16 A
Switching Capability Voltage	400 V
Breaking Capacity Current	16 A
The Recommended Maximum Load	16 A/400 V AC-1; 3,6 A/110 V DC-13
Surge Current (20Ms)	40 A
Bounce Time	3
Release Time Kontaktstudtid	11 ms
IP Class	IP40
Isolation Contact / Contact	4000 V
Isolation Contact / Coil	4000 V
Insulation Class EN60947	500 V, Pollution 3, Group C
Temperature range from	-40 °C

Temperature range bearing, from	-40 °C
Temperature range bearing, to	80 °C
Temperature range to	60 °C
Frequency	50 Hz
Optional Coil	DX (diode + LED)
Weight	90 g
Approvals	CE, UL, RoHS, CSA, Gost R

