

## C4 INDUSTRIAL RELAY

4-pole 10 A

C4-A40110D  
 Relay 14 Pin 4 Pole 110V dc

- Marking system that can be custom-marked at factory
- Colour-coded test button, both lockable and spring-loaded
- Mechanical indication, double windows



### PRODUCT DESCRIPTION

### SPECIFICATIONS

|                              |                                   |
|------------------------------|-----------------------------------|
| Nominal power dc             | 1.4 W                             |
| Coil Voltage DC              | 110 V DC                          |
| OFF-Voltage Un Max           | 0.1                               |
| Number Of Contacts           | 4                                 |
| Contact Material             | AgNi                              |
| Switching Capability Voltage | 250 V                             |
| Breaking Capacity Current    | 10 A                              |
| The Recommended Maximum Load | 10 A/250 V AC-1; 0,5 A/110 V DC-1 |
| Recommended Min Load         | 10 mA/5 V                         |
| Resistive Load 110 V DC Max  | 55 W                              |
| Resistive Load 24 V dc Max   | 240 W                             |
| Surge Current (20Ms)         | 30 A                              |
| Bounce Time                  | 3                                 |
| Release Time                 | 8 ms                              |
| Release Time Kontaktstudtid  | 9 ms                              |
| IP Class                     | IP40                              |
| Isolation Contact / Contact  | 2500 V                            |

|                                 |                                |
|---------------------------------|--------------------------------|
| Isolation Contact / Coil        | 2500 V                         |
| Insulation Class EN60947        | 250 V Pollution 3, Group C     |
| Temperature range from          | -40 °C                         |
| Temperature range bearing, from | -40 °C                         |
| Temperature range bearing, to   | 80 °C                          |
| Temperature range to            | 60 °C                          |
| Frequency                       | 50 Hz                          |
| Weight                          | 90 g                           |
| Approvals                       | CCC, Gost R, Lloyd's, CE, RoHS |

