

## C4 INDUSTRIAL RELAY

4-pole 10 A

C4-A40125D

Relay 14 Pin 4 Pole 125V dc

- Marking system that can be custom-marked at factory
- Colour-coded test button, both lockable and spring-loaded
- Mechanical indication, double windows



### PRODUCT DESCRIPTION

### SPECIFICATIONS

|                              |                                   |
|------------------------------|-----------------------------------|
| Nominal power dc             | 1.4 W                             |
| Coil Voltage DC              | 125 V DC                          |
| OFF-Voltage Un Max           | 0.1                               |
| Number Of Contacts           | 4                                 |
| Contact Material             | AgNi                              |
| Switching Capability Voltage | 250 V                             |
| Breaking Capacity Current    | 10 A                              |
| The Recommended Maximum Load | 10 A/250 V AC-1; 0,5 A/110 V DC-1 |
| Recommended Min Load         | 10 mA/5 V                         |
| Resistive Load 110 V DC Max  | 55 W                              |
| Resistive Load 24 V dc Max   | 240 W                             |
| Surge Current (20Ms)         | 30 A                              |
| Bounce Time                  | 3                                 |
| Release Time                 | 8 ms                              |
| Release Time Kontaktstudtid  | 9 ms                              |
| IP Class                     | IP40                              |
| Isolation Contact / Contact  | 2500 V                            |

