

C4 INDUSTRIAL RELAY

4-pole 10 A

C4-A40DX24D

Relay 14 Pin 4 Pole Diode LED 24V dc

- Marking system that can be custom-marked at factory
- Colour-coded test button, both lockable and spring-loaded
- Mechanical indication, double windows



PRODUCT DESCRIPTION

SPECIFICATIONS

Nominal power dc	1.4 W
Coil Voltage DC	24 V DC
OFF-Voltage Un Max	0.1
Number Of Contacts	4
Contact Material	AgNi
Switching Capability Voltage	250 V
Breaking Capacity Current	10 A
The Recommended Maximum Load	10 A/250 V AC-1; 0,5 A/110 V DC-1
Recommended Min Load	10 mA/5 V
Resistive Load 110 V DC Max	55 W
Resistive Load 24 V dc Max	240 W
Surge Current (20Ms)	30 A
Bounce Time	3
Release Time	8 ms
Release Time Kontaktstudtid	9 ms
IP Class	IP40
Isolation Contact / Contact	2500 V

Isolation Contact / Coil	2500 V
Insulation Class EN60947	250 V Pollution 3, Group C
Temperature range from	-40 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	80 °C
Temperature range to	60 °C
Frequency	50 Hz
Optional Coil	DX (diode + LED)
Weight	90 g
Approvals	CCC, Gost R, Lloyd's, CE, RoHS

