

LEVEL CONTROL RELAY ENR

84870200

LEVEL CONTROL ENR

- Regulation of 2 levels
- Filling/emptying function
- Mittaus johtavilla elektrodeilla. Leveys 22,5 mm
- Sensitivity adjustable 5 k Ω - 100 k Ω
- 24-240 V AC/DC



PRODUCT DESCRIPTION

KEY FEATURES

- Regulation of 1 or 2 levels (min / max)
- Monitoring filling (UP) or emptying (DOWN) selected by a switch on the front panel
- Probes supplied with AC current
- Time delay preventing wave effect adjustable from 0.1 to 5s (ENRM)
- Sensitivity adjustable on front panel from 250 Ω to 1 M Ω (ENRM)
- Sensitivity adjustable on front panel from 5 K Ω to 100 k Ω (ENR)

SPECIFICATIONS

Approvals	CE, CSA, RoHS, UL
Breaking capacity	8A, 250V AC
Electrode Current	1 mA
Electrode Voltage	12 V AC
IP Class Connection	IP20
IP Class Housing	IP30
Operating Voltage AC / DC Max	264 V
Supply Voltage AC / DC Min	20.4 V
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-20 °C
Temperature range to	50 °C

Weight 91 g

Width 22.5 mm

