C9 MINIATURE RELAY

4-pole 5 A

C9A4124A
Relay 14 Pin 4 Pole 0.2µ Au 24V ac



- Colour-coded test button, both lockable and non-locking
- Marking system
- Mechanical indication

PRODUCT DESCRIPTION

SPECIFICATIONS

Working Un	0,8-1,1
Nominal power ac	1.2 VA
Coil Voltage AC	24 V AC
OFF-Voltage Un Max	0.25

Number Of Contacts	4
Contact Material	AgNi + 0,2 µ Au
Switching Capability Voltage	250 V
Breaking Capacity Current	5 A
The Recommended Maximum Load	5 A/250V AC-1; 5 A/30 V DC-1
Recommended Min Load	10 mA/10 V
Resistive Load 110 V DC Max	50 W
Resistive Load 24 V dc Max	100 W
Surge Current (20Ms)	15 A
Release Time	6 ms
Release Time Kontaktstudstid	7 ms

IP Class	IP40
Isolation Contact / Contact	2500 V
Isolation Contact / Coil	2000 V

Temperature range from	-40 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	80 °C
Temperature range to	60 °C
Frequency	50 Hz
Weight	43 g
Approvals	CE, Gost R, RoHS, CCC, CSA, Lloyd´s, UL











