

C9 MINIATURE RELAY

4-pole 5 A

C9A42110D

Relay 14 Pin 4 Pole 10 μ Au 110V dc

- Colour-coded test button, both lockable and non-locking
- Marking system
- Mechanical indication



PRODUCT DESCRIPTION

SPECIFICATIONS

Working Un	0,8-1,1
Nominal power dc	1 W
Coil Voltage DC	110 V DC
OFF-Voltage Un Max	0.25
Number Of Contacts	4
Contact Material	AgNi + 10 μ Au
Switching Capability Voltage	250 V
Breaking Capacity Current	5 A
The Recommended Maximum Load	5 A/250V AC-1; 5 A/30 V DC-1
Recommended Min Load	1 mA/1 V
Resistive Load 110 V DC Max	50 W
Resistive Load 24 V dc Max	100 W
Surge Current (20Ms)	15 A
Release Time	6 ms
Release Time Kontaktstudstid	7 ms
IP Class	IP40

Isolation Contact / Contact	2500 V
Isolation Contact / Coil	2000 V
Temperature range from	-40 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	80 °C
Temperature range to	60 °C
Frequency	50 Hz
Weight	43 g
Approvals	CE, Gost R, RoHS, CCC, CSA, Lloyd's, UL

