

C9 MINIATURE RELAY

4-pole 5 A

C9E2124D

Relay QRC 2-pole 24VDC (500mW)

- Colour-coded test button, both lockable and non-locking
- Marking system
- Mechanical indication



PRODUCT DESCRIPTION

SPECIFICATIONS

Working Un	0,8-1,70
Nominal power dc	0.5 W
Coil Voltage DC	24 V DC
OFF-Voltage Un Max	0.2
Number Of Contacts	2
Contact Material	AgNi + 0,2 µ Au
Switching Capability Voltage	250 V
Breaking Capacity Current	5 A
The Recommended Maximum Load	5 A/250V AC-1; 5 A/30 V DC-1
Recommended Min Load	10 mA/10 V
Resistive Load 110 V DC Max	50 W
Resistive Load 24 V dc Max	100 W
Surge Current (20Ms)	15 A
Release Time	6 ms
Release Time Kontaktstuds tid	7 ms
IP Class	IP40
Isolation Contact / Contact	2500 V

Isolation Contact / Coil	2500 V
Temperature range from	-40 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	80 °C
Temperature range to	60 °C
Frequency	50 Hz
Weight	40 g
Approvals	CE, Gost R, RoHS, CCC, CSA, Lloyd's, UL

