

C3 INDUSTRIAL RELAY

3-pole 10 A

C3-A30DX12D

Relay MRC 3-pole 12VDC LED==diode==

- Colour-coded test button
- Marking system that can be custom-marked at factory
- Mechanical indication, double windows



PRODUCT DESCRIPTION

SPECIFICATIONS

Working Un	0,8-1,1
Nominal power dc	1.3 W
Coil Voltage DC	12 V DC
OFF-Voltage Un Max	0.1
Number Of Contacts	3
Contact Material	AgNi
Switching Capability Voltage	250 V
Breaking Capacity Current	10 A
The Recommended Maximum Load	10 A/250 V AC-1; 0,5 A/110 V DC-1
Recommended Min Load	10 mA/10 V
Resistive Load 110 V DC Max	55 W
Resistive Load 24 V dc Max	240 W
Surge Current (20Ms)	30 A
Release Time	8 ms
Release Time Kontaktstuidtid	9 ms

IP Class	IP40
Isolation Contact / Contact	2500 V
Isolation Contact / Coil	2500 V
Insulation Class EN60947	250 V, Pollution 3, Group C
Temperature range from	-40 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	80 °C
Temperature range to	60 °C
Frequency	50 Hz
Optional Coil	DX (diode + LED)
Weight	81 g
Approvals	CE, Gost R, RoHS, CCC, CSA, Lloyd's, UL

