

## C3 INDUSTRIAL RELAY

3-pole 10 A

C3-M10X24D

Relay MRC 1-pole, NO LEDmagnetic b,24VDC

- Colour-coded test button
- Marking system that can be custom-marked at factory
- Mechanical indication, double windows



### PRODUCT DESCRIPTION

### SPECIFICATIONS

|                              |                                  |
|------------------------------|----------------------------------|
| Working Un                   | 0,8-1,1                          |
| Nominal power dc             | 1.3 W                            |
| Coil Voltage DC              | 24 V DC                          |
| OFF-Voltage Un Max           | 0.1                              |
| Number Of Contacts           | 1                                |
| Contact Material             | AgNi                             |
| Switching Capability Voltage | 250 V                            |
| Breaking Capacity Current    | 10 A                             |
| The Recommended Maximum Load | 10 A/250 V AC-1; 10 A/220 V DC-1 |
| Surge Current (20Ms)         | 30 A                             |
| Release Time                 | 10 ms                            |
| Release Time Kontaktstudtid  | 11 ms                            |
| IP Class                     | IP40                             |
| Isolation Contact / Contact  | 2500 V                           |
| Isolation Contact / Coil     | 2500 V                           |

|                                 |                             |
|---------------------------------|-----------------------------|
| Insulation Class EN60947        | 250 V, Pollution 3, Group C |
| Temperature range from          | -40 °C                      |
| Temperature range bearing, from | -40 °C                      |
| Temperature range bearing, to   | 80 °C                       |
| Temperature range to            | 70 °C                       |
| Frequency                       | 50 Hz                       |
| Optional Coil                   | X (LED)                     |
| Weight                          | 90 g                        |
| Approvals                       | CE, Gost R, RoHS, CCC       |

