

C3 INDUSTRIAL RELAY

3-pole 10 A

C3-N3424D

Relay MRC 3-pole 800MW==Au== 24VDC

- Colour-coded test button
- Marking system that can be custom-marked at factory
- Mechanical indication, double windows



PRODUCT DESCRIPTION

SPECIFICATIONS

Working Un	0,8-1,1
Nominal power dc	0.8 W
Coil Voltage DC	24 V DC
OFF-Voltage Un Max	0.1
Number Of Contacts	3
Contact Material	AgNi
Switching Capability Voltage	250 V
Breaking Capacity Current	6 A
The Recommended Maximum Load	6 A/250 V AC-1; 6 A/30 V DC-1
Recommended Min Load	10 mA/10 V
Resistive Load 24 V dc Max	144 W
Surge Current (20Ms)	15 A
Release Time	10 ms
Release Time Kontaktstudtid	11 ms
IP Class	IP40

Isolation Contact / Contact	2500 V
Isolation Contact / Coil	2500 V
Insulation Class EN60947	250 V, Pollution 3, Group C
Temperature range from	-40 °C
Temperature range bearing, from	-40 °C
Temperature range bearing, to	80 °C
Temperature range to	60 °C
Frequency	50 Hz
Weight	90 g
Approvals	CE, Gost R, RoHS, CCC, CSA

