

3 PHASE, PHASE CONTROL MWS, MWS2

84873029

MWS PHASE CONTROL RELAY

- Triggers alarm upon incorrect phase sequence/phase interruption
- Wide range input voltage from 3x208-480 V ac
- 17.5 mm cabinet with DIN rail
- LED indication
- Does not measure returned voltage



PRODUCT DESCRIPTION

Control relay for 3-phase network that monitors the phase sequence for phases L1, L2 and L3 and checks whether one or more phases are lacking. As long as the phase sequence and voltages are correct (>183 V AC), the output relay(s) is closed and the yellow LED (LED indication) is on. If a phase sequence or phase interruption fault occurs, the relay drops out and the LED turns off. Does not measure returned voltage.

SPECIFICATIONS

Approvals	CSA, GL, RoHS, UL
Breaking capacity	8A @ 250V AC, 8A @ 30V DC
IP Class Connection	IP20
IP Class Housing	IP30
Output	Relay
Supply voltage	3 x 208-480V AC
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-20 °C
Temperature range to	50 °C
Time Delay On Crossing The Threshold	0.1 s
Time Delay Start	0.5 s
Weight	80 g

