LCIS MECHANICAL RELAY

Gold-plated contacts

760020.1010
Interfacerelay 24V Gouldplated.



- Jumper connection for easy installation
- Connection from top of the relay
- 6 A/1 mA
- Push-in or screw termination

PRODUCT DESCRIPTION

Lütze LCIS relay range offers compact design along with excellent usability. These relays are only 6,2mm wide and 90mm tall which makes them very compact and easy to install even in confined enclosures. LCIS relays can be installed in any position. All terminals (A1, A2 etc.) distinctively marked and additionally they can be identified by using standard 5x5mm or 6x12mm markers. All terminals can be connected with jumper combs connecting up to 16 poles. Push-in and screw terminals available.

SPECIFICATIONS

Load Current AC max	6 A
Load Current DC max	6 A
Load Voltage AC min	1 V
Load Voltage AC max	250 V
Load Voltage DC min	1 V
Load Voltage DC max	250 V

Width	6.2 mm
Temperature range from	-25 °C
Temperature range to	60 °C
Weight	35 g
Approvals	CE, cULus, DNV, GL, RoHS

Switching Current Max	6 A

Power consumption	11 mA
Power Supply DC min	19.2 V
Power Supply DC max	30 V
Contact Material	AgSnO2 + 5 µm HV
Cross Section Max	2.5 mm²
Cross section min	0.25 mm²
Depth	93 mm
Insulation In	4000 V
Insulation Out	4000 V
IP Class	IP20
Height	76 mm
Load Current AC min (mA)	1 mA
Load Current DC min (mA)	1 mA





