

## POWER SUPPLY 1-PHASE, 5 V DC MINILINE SERIES

ML30.241  
PULS PSU 30W 24-28VDC

- Output current 3 A and 5 A
- Up to 80% efficiency
- AC and dc input voltage
- Width of 22.5 mm
- 5 V, 12 V and 24 V DC options



### PRODUCT DESCRIPTION

3 A model included in Pulse series Mini Line 2 is the latest development series of small power supplies with very compact dimensions and low weight. The units have high efficiency, low EMC interference and good protection against mains transients. This makes them useful in almost all electrical environments and are a great addition to the earlier Mini Line series.


Very low quiescent current and high efficiency even at loads down to 60% makes the aggregates at a good energy and environmental choices.

5 A model is included in the earlier series Miniline having a very proven design and spring terminals for the best connection.


For good cooling free space of 40 mm above and 20 mm under the power supply is recommended. The sides 0 mm unless neighbouring products are a heat source, for example, a power supply unit. Leave then a 15 mm air gap

#### Output characteristics

ML15.051 (3 A)



ML30.101 (5A)



## SPECIFICATIONS

Input voltage range	Wide-range
Number of phases	1
Input voltage AC	100-240 V
Input voltage ac min	85 V AC
Input voltage ac max	264 V AC

<b>Input voltage DC</b>	110-300 V
<b>Input voltage dc min</b>	88 V DC
<b>Input voltage dc max</b>	375 V DC
<b>Inrush current at 120 V ac typical</b>	18 A
<b>Inrush current at 230 V ac typical</b>	35 A
<b>Power Factor at 120 V AC, full load. Typical</b>	0.52
<b>Power Factor at 230 V AC, full load. Typical</b>	0.49
<b>Supply Frequency</b>	50-60 ±6 %
<b>Power Consumption At 120 V AC</b>	0.54 A
<b>Power Consumption At 230 V AC</b>	0.3 A
<b>Type Power Supply</b>	AC-DC
<b>Output voltage</b>	24 V DC
<b>Output voltage min</b>	24 V DC
<b>Output voltage max</b>	28 V DC
<b>Output Current</b>	1.3 A
<b>Effect</b>	30 W
<b>Power Reduction Of 60 To 70 ° C</b>	0.8 W/°C
<b>Ripple. max</b>	50 mV pp
<b>Temperature Range Without Derating From</b>	-10 °C
<b>Temperature Range Without Derating To</b>	60 °C
<b>Efficiency At 120 V AC, full load. Typical</b>	88 %
<b>Efficiency At 230 V AC, full load. Typical</b>	89.4 %
<b>Lifetime at 120 V ac, full load and +40 ° C</b>	171000 h
<b>Lifetime at 230 V ac, full load and +40 ° C</b>	174000 h
<b>MTBF (IEC 61709) 230 V AC, Maximum Load, 40 ° C</b>	2405000 h
<b>Width</b>	22.5 mm
<b>Height</b>	75 mm
<b>Depth</b>	91 mm
<b>Weight</b>	0.14 kg
<b>Clamp type</b>	Screw on

<b>Series</b>	Miniline
<b>Approvals</b>	ABS, CB, CE, CSA, GL, NEC Class 2, UL
<b>Material Protection</b>	ABS plastic
<b>Hold-up time at 120 V AC, full load. Typical.</b>	31 ms
<b>Hold-up time at 230 V AC, full load. Typical.</b>	141 ms
<b>IP Class</b>	IP20
<b>Active Transient</b>	Yes

