

## POWER SUPPLY 1-PHASE, 24 V DC, DIMENSION C SERIES, GENERATION 2

CP5.241-S2

PSU 100-240V ac I/P 24V dc 5A 120W O/P Push-In

- Output current 5 A
- Efficiency up to 94.3%
- 20% power reserve
- Only 32mm wide



### PRODUCT DESCRIPTION

The Dimension CP-Series are cost optimized power supplies without compromising quality, reliability and performance. The CP-Series is part of the DIMENSION power supply family.

The CP5.241 power supplies come with three connection terminal options: screw, spring-clamp or push-in terminals, which are optimized for automated wiring. The CP5.241-C1 is equipped with conformal coated pc-boards preferred for the use in harsh environments and the CP5.242 features an enhanced DC input voltage range.

The most outstanding features of these units are the small size, the high efficiency, the electronic inrush current limitation, active PFC and the wide operational temperature range. The devices have a power reserve of 20% included, which may even be used continuously at temperatures up to +45°C. Additionally, they can deliver 3 times the nominal output current for 12ms which helps to trip fuses on faulty output branches.

High immunity to transients and power surges as well as low electromagnetic emission, a DC-OK signal contact for remote monitoring, and a large international approval package for a variety of applications makes this unit suitable for nearly every situation.

- AC 100-240V Wide-range Input
- Width only 32mm
- Efficiency up to 94.3%
- Excellent Partial Load Efficiency
- 20% Output Power Reserves
- EasyFuse Breaking – 3 times nominal current for 12ms
- SafeHiccupPLUS Overload Mode
- ActivePower Factor Correction (PFC)
- Minimal Inrush Current Surge
- Full Power Between -25°C and +60°C
- DC-OK Relay Contact
- 3 Year Warranty

### SPECIFICATIONS

Input voltage range	Wide-range
Number of phases	1
Input voltage AC	100-240 V
Input voltage ac min	85 V AC

<b>Input voltage ac max</b>	264 V AC
<b>Input voltage DC</b>	110-150 V
<b>Input voltage dc min</b>	88 V DC
<b>Input voltage dc max</b>	180 V DC
<b>Inrush current at 120 V ac typical</b>	5 A
<b>Input current at 230 V ac typical</b>	6 A
<b>Power Factor at 120 V AC, full load. Typical</b>	0.98
<b>Power Factor at 230 V AC, full load. Typical</b>	0.91
<b>Supply Frequency</b>	50-60 ±6 %
<b>Power Consumption At 120 V AC</b>	1.09 A
<b>Power Consumption At 230 V AC</b>	0.6 A
<b>Type Power Supply</b>	AC-DC
<b>Output voltage</b>	24 V DC
<b>Output voltage min</b>	24 V DC
<b>Output voltage max</b>	28 V DC
<b>Output Current</b>	5 A
<b>Effect</b>	120 W
<b>Power Reduction Of 60 To 70 ° C</b>	3 W/°C
<b>Ripple. max</b>	50 mV pp
<b>Temperature Range Without Derating From</b>	-25 °C
<b>Temperature Range Without Derating To</b>	60 °C
<b>Efficiency At 120 V AC, full load. Typical</b>	93.6 %
<b>Efficiency At 230 V AC. Typical</b>	92 %
<b>Efficiency At 230 V AC, full load. Typical</b>	94.3 %
<b>Lifetime at 120 V ac, full load and +40 ° C</b>	143000 h
<b>Lifetime at 230 V ac, full load and +40 ° C</b>	166000 h
<b>MTBF (IEC 61709) 230 V AC, Maximum Load, 40 ° C</b>	876000 h
<b>Width</b>	32 mm
<b>Height</b>	124 mm
<b>Depth</b>	102 mm
<b>Weight</b>	0.44 kg

Clamp type	Push in
Series	Dimension C
Approvals	ATEX, CE, cULus, IECEx, IEC 62368-1:2018
DC relay output	Yes
Material Protection	Aluminium
Hold-up time at 120 V AC, full load. Typical.	35 ms
Hold-up time at 230 V AC, full load. Typical.	35 ms
IP Class	IP20
Active Transient	Yes



