

HEATER 10-20W - CSK 060

CSK

06040.0-00

CSK 060 10W Touch-Safe Heater, 120-240V ac/dc



- Dual isolated (does not require earthing)
- Innovative design and small size
- Low element surface temperature
- Quick installation, bracket for DIN rail



PRODUCT DESCRIPTION

A small, powerful 20 W heater. It is easily installed thanks to the mounting clips for DIN rails that are fitted on the back of the heaters.

Because the heater is dual isolated with a plastic casing, the side surfaces' temperature never exceeds 85 °C, so the heater can be mounted relatively close to other components in the same installation, and there is no risk for fire damage.

The dual isolation also means that the heater does not need to be earthed.

The heat source consists of a PTC element, which provides a long and reliable lifetime even if the heater is in constant operation.

SPECIFICATIONS

Approvals	CE, EAC, Gost R, RoHS, UL E150057, VDE
Depth	75 mm
Heat Output	10 W
Heater	Plastic
Height	98 mm
Humidity Storage	<90% RH
IP Class	IP20
Nominal voltage	120-240 V AC/DC
Operating Humidity	< 90% RH
Operational Temperature	-45°C ... +70°C
Pre fuse (slow)	2 A
Protection Class	II (double insulated)
Starting Current Max	1 A

Storage temperature	-45°C ... +70°C
Weight	0.2 kg
Width	38 mm
Voltage max	265 V ac/dc
Voltage min	110 V ac/dc

Example of connection

