

## TAMPER-PROOF THERMOSTAT - FTO 011/FTS 011

FTO, FTS

01160.0-00  
FTO 011 Thermostat, 15°C / 5°C (off/on), normally closed



- Small size
- Preset values
- Simple installation
- Innovative design

### PRODUCT DESCRIPTION

Tamper-proof (Pre-set) Thermostat FTO 011: Normally closed - Contact breaks (red casing) for regulating heaters or for switching signal devices when temperature has fallen below the minimum value. The contact opens when temperature is rising.

Tamper-proof (Pre-set) Thermostat FTS 011: Normally open - Contact makes (blue casing) for regulating filter fans, heat exchangers, cooling devices or for switching signal devices when temperature limit has been exceeded. The contact closes when temperature is rising.

## SPECIFICATIONS

Approvals	CE, CSA, cULus, EAC, EMC, RoHS, UL E164102, VDE
Contact resistance	<20 mΩ
Control range temperature from	41 °F
Control range temperature to	15 °C
Depth	33 mm
Height	47 mm
Inrush Max	16 A
IP Class	IP20
Material Plastic Housing	Plastic
Operational Temperature	-40°C ... +80°C
Storage temperature	-45°C ... +80°C
Switch off temperature NC	15 °C
Switch on temperature NC	5 °C
Tolerance for switch on	±5K
Tolerance switch off	±5K

<b>Weight</b>	0.023 kg
<b>Width</b>	33 mm
<b>Voltage max</b>	250 V ac

