

## TAMPER-PROOF THERMOSTAT - FTO 011/FTS 011

FTO, FTS

01160.0-01

FTO 011 Thermostat, 25°C / 15°C (off/on), normally closed

- Small size
- Preset values
- Simple installation
- Innovative design



### PRODUCT DESCRIPTION

Tamper-proof (Pre-set) Thermostat FTO 011: Normally closed - Contact breaks (red casing) for regulating heaters or for switching signal devices when temperature has fallen below the minimum value. The contact opens when temperature is rising.

Tamper-proof (Pre-set) Thermostat FTS 011: Normally open - Contact makes (blue casing) for regulating filter fans, heat exchangers, cooling devices or for switching signal devices when temperature limit has been exceeded. The contact closes when temperature is rising.

### SPECIFICATIONS

Approvals	CE, CSA, cULus, EAC, EMC, RoHS, UL E164102, VDE
Contact resistance	<20 mΩ
Control range temperature from	59 °F
Control range temperature to	25 °C
Depth	33 mm
Height	47 mm
Inrush Max	16 A
IP Class	IP20
Material Plastic Housing	Plastic
Operational Temperature	-40°C ... +80°C
Storage temperature	-45°C ... +80°C
Switch off temperature NC	25 °C
Switch on temperature NC	15 °C

<b>Tolerance for switch on</b>	±5K
<b>Tolerance switch off</b>	±5K
<b>Weight</b>	0.023 kg
<b>Width</b>	33 mm
<b>Voltage max</b>	250 V ac

