SOLIOS EV-CL CAMERA LINK FRAME GRABBER

MIL-LITEXLNX

- Frame grabber with available support for 10-taps
- Captures from frame and line scan cameras
- Programmable FPGA (optional)
- PCI Express x4 interface



PRODUCT DESCRIPTION

Matrox Solios eV-CL ushers in a new level of value for Camera Link® frame grabbers. It provides connectivity to the most high-performance, multi-megapixel area and line scan Camera Link® cameras on the market augmented with onboard Bayer interpolation (eV-CLB/CLBL), color space conversions and look-up tables. The Matrox Solios eV-CL provides all these capabilities at the most attractive price point yet.


Technical specifications

Connectivity (ev-CLB/CLF)	Connectivity (ev-CLBL/CLFL)


• two(2) mini Camera Link® (HDR) connectors
• one (1) DBHD-15 male connector
  • three (3) TTL configurable auxiliary I/Os
  • two (2) LVDS auxiliary inputs
  • one (1) LVDS auxiliary output
  • two (2) opto-isolated auxiliary inputs
• optional add on DBHD-15 male connector
  • three (3) TTL configurable auxiliary I/Os
  • two (2) LVDS auxiliary inputs
  • one (1) LVDS auxiliary output
  • two (2) opto-isolated auxiliary inputs
• optional add on DB-91 female connector
  • one (1) TTL configurable auxiliary I/O
  • one (1) LVDS auxiliary input
  • two (2) opto-isolated auxiliary inputs
	• two(2) Camera Link® (MDR) connectors
	• one DB-44 and DB-9 connector
	  • six (6) TTL configurable auxiliary I/Os
	  • four (4) LVDS configurable auxiliary inputs
	  • four (4) LVDS configurable auxiliary outputs
	  • separate LVDS pixel clock, hsync and vsync outputs
	  • four (4) opto-isolated configurable auxiliary inputs

Block diagram


Matrox Solios eV-CLB



Matrox Solios eV-CLBL



Matrox Solios eV-CLF



Matrox Solios eV-CLFL

