

## MOLEX - MPM DIN FORM A LOW HOUSING / HIGH HOUSING

C28200N0R

DIN A connector 2P+ground, Ext thread, IP67, Black

- With or without LED and transient protection
- Fibreglass-reinforced housing
- Turnable insert
- EN175301-803 (DIN43650)-A



### PRODUCT DESCRIPTION

Standard internal thread DIN valve connector, IP65 rated. Available with different thread style, gaskets and circuitry. Conforms to EN 175301-803.

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the PG9 and PG11 internal thread connector cable range. Conforms to EN 175301-803.

### SPECIFICATIONS

Circuit	No circuit
IP Class	IP67
Cross-Section Max	1.5 mm <sup>2</sup>
Cable Diameter Max	9 mm
Cable Diameter Min	4 mm
Color House	Black
Central Material	Polyamide
LED indicator	No
Connector	DINA 43650
Temperature range to	90 °C
Temperature range from	-40 °C
Current max	16 A
Rated voltage	250 V AC/300 V DC
Packing Materials	NBR

Colour LED

No LED

Screw and Gasket

Integrated NBR Gasket & IP67 screw

Manufacturer Part No

1212010001

