

## MOLEX - MPM DIN FORM A IP67 MOULDED CABLE CONNECTOR

E152P3N3001P

DINA cordset 2+earth 3m PUR 3x0,75



- Fully overmoulded providing a high level of protection
- With or without LED and transient protection
- Integrated gasket and screw, IP67
- EN175301-803 (DIN43650)-A
- 2 pole or 3 pole + earth

### PRODUCT DESCRIPTION

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the internal thread connector cable range. Conforms to EN 175301-803.

### SPECIFICATIONS

<b>Cable length</b>	3000 mm
<b>Material Cable</b>	PUR
<b>Circuit</b>	No circuit
<b>Halogen free</b>	No
<b>IP Class</b>	IP67
<b>Cross-Section</b>	0.75 mm <sup>2</sup>
<b>Cable diameter</b>	6,5
<b>Color Cable</b>	Black
<b>Color House</b>	Black
<b>LED indicator</b>	No
<b>Temperature range to</b>	90 °C
<b>Temperature range from</b>	-40 °C
<b>Current max</b>	5 A
<b>Rated voltage</b>	250 V
<b>Screw size</b>	M3x27
<b>Packing Materials</b>	NBR
<b>Colour LED</b>	No LED
<b>Screw and Gasket</b>	NBR integrated gasket assembled + IP67 screw

