



SURFACE MOUNTED SIREN BU1/ PANEL MOUNTED BUZZER BU2/BU3

B100510004

Panel BUZZERBU1 12VDC

- High noise level 108 dB
- IP66 embedded cable



PRODUCT DESCRIPTION

BU2/BU3

- Quick and easy installation
- Adjustable noise level at front (approx. 10 dB)
- Pulsating sound

APPLICATION AREA BU1

Surface mounted buzzer with high sound level and high IP-class. With its embedded cable, the siren is easily fitted on the machine without any encapsulation.

APPLICATION AREA BU2/BU3

Small panel mounted buzzer with flat terminal connection. The sound is easily adjusted through a window at the front and the sound can be trimmed up to approx. 10 dB

SPECIFICATIONS

| | |
|---------------------|--------|
| Color House | Black |
| Diameter | 60 mm |
| IP Class | IP66 |
| Mounting | Screw |
| Nominal current max | 0,3 A |
| Nominal current min | 0,3 A |
| Number of tones | 1 |
| Sound level max | 108 dB |
| Sound level min | 108 dB |
| Supply Voltage | 12 V |

| | |
|------------------------|---------|
| Supply Voltage DC Max | 15 V DC |
| Supply Voltage DC Min | 6 V DC |
| Temperature range from | -20 °C |
| Temperature range to | 70 °C |
| Tone frequency max | 2400 Hz |
| Tone frequency min | 2200 Hz |
| Weight | 110 g |

