

## SIGNAL TOWER Ø 70MM PC7

910111405 PC7DCB, Top LED steady/flashing module, amber, 24 V AC/DC

- · Modular signal tower
- Ø 70 mm, Polycarbonate black
- Polycarbonate, amber, red, clear, blue, green, yellow or magenta
- LED steady beacon, LED flashing beacon, LED rotating beacon or LED multi colour beacon



## PRODUCT DESCRIPTION

The PC7 range of modular signal towers uses the highest quality components which are 6 times brighter than the competition.

Offers a complete range of bright LED modules with several function modes allowing you to have multi colour lights in 7 colours which can be switched externally (red, yellow, green, blue, clear, magenta and turquoise)

Multi tone siren modules use DIP switches enabling you to select one of eight tones.

Comprehensive range of mounting options including quick mount solutions whilst offering different tube lengths.

Each module allows to have a diffusor without altering the signalling effect, choosing between a clear or a diffuse signal tower appearance.

The M12 connector base accessory can be used for applications which need quick and cost effective installation.



Color House	Black
Color Lens	Orange
Diameter	70 mm
IP Class	IP66
Light source	LED
Light type	Amber LED
Nominal current max	0.1 A
Supply Voltage	24 V
Temperature range from	-30 °C
Temperature range to	70 °C
Weight	86 g







