



AUDIO GENERATOR EHS/EHF/EHL

730010405

EHL-D Elect. Sound Generator 12-24VACDC

- Electronic audio generator
- up to 118 dB
- IP65
- For demanding use




PRODUCT DESCRIPTION

Powerful aluminium cast audio generator for demanding operating conditions. For both inside and outside use. 15 different sounds. Special models on request.

TECHNICAL SPECIFICATIONS

Sound volume (from 1 m distance)	118 dB, 15 different sounds
Material, casing	Aluminium, epoxy powder coated
Strand size	2.5 mm ²
Operating temperature	-30 °C...+60 °C
Voltage	12-24 V AC/DC, 230-240 V AC (Other voltages on order)
Current consumption	600 mA (24 V AC/DC) 40 mA (230 V AC)
IP-class	IP65
Approvals	CE, EMC, LVD

DIMENSIONS



ORDER NUMBERS

Order number	Description	Sound volume	Voltage
730010405	EHL-D	108 dB	12-24 V AC/DC
730010313	EHL-D	108 dB	230-240 V AC
731010405	EHS-D	118 dB	12-24 V AC/DC
731010313	EHS-D	118 dB	230-240 V AC
731110405	EHF-D	118 dB	12-24 V AC/DC
731110313	EHF-D	118 dB	230-240 V AC

SPECIFICATIONS

IP Class	IP66
Sound level max	118 dB
Supply Voltage DC Max	24 V DC
Supply Voltage DC Min	12 V DC
Temperature range from	-30 °C
Temperature range to	60 °C