



AUER EX-CLASSED SIGNAL HORN DHH

300000213

dHH Ex-proof-SIGNAL HORN 230VAC 60Hz

- Strong signal horn, 105 dB
- Fits zone 1, 2, 21 and 22
- Insulation class II - no potential equalization required
- IP66, -20 to +75 °C



PRODUCT DESCRIPTION

Strong horn with typical horn signal.

For use in areas exposed to explosions in zones 1 and 2.

Modular system with synthetic cover made of fiberglass reinforced polyester.

Flame-proof chamber "d"

The security-class connection chamber increased safety "e".

Lower weight - robust and corrosion proof construction.

Insulation class II - no potential equalization required.

DC models with electronic switches - significantly longer service life.

SPECIFICATIONS

| | |
|---------------------------------|----------------|
| Color House | Black RAL 9005 |
| Diameter | 190mm |
| IP Class | IP66 |
| Mounting | Independent |
| Nominal current max | 0.07 A |
| Nominal current min | 0.07 A |
| Number of tones | 1 |
| Operating Voltage AC Max | 253 V AC |
| Operating Voltage AC Min | 195.5 V AC |
| Sound control | No |
| Sound level max | 105 dB |

| | |
|------------------------|---------|
| Supply Voltage | 230 V |
| Temperature range from | -50 °C |
| Temperature range to | 70 °C |
| Terminal connection | 2.5 mm² |
| Weight | 5500 g |