

## **AUER - PANEL MOUNTED BUZZER**

812510313 ESV BUZZER 30mm 230VAC

- Panel mounted buzzer with loud sound level
- Adjustable volume
- 3 selectable sound signals
- For mounting in drilled holes 22.5 mm or 30.5 mm



## PRODUCT DESCRIPTION


Panel mounted buzzer with wide voltage range and high enclosure class, IP65. Excellent when you want to call for extra attention in a panel.

## **SPECIFICATIONS**

Color House	Black
Diameter	30 mm
IP Class	IP65
Nominal current max	0.04 A
Number Of Optional Modules	0
Number of tones	2
Sound level max	85 dB
Sound level min	80 dB
Supply Voltage AC / DC Min	10 V
Temperature range from	-25 °C
Temperature range to	60 °C
Terminal connection	2.5 mm²
Tone frequency max	3500 Hz
Weight	30 g

The sound the distance Indication, a direction, hu sound press	the s als imidit	folio o fac y, we	wing ctors eather	dist like	tone	tab type	ile is	to b	e se eed,	en a win	s d									
Distance (m)	77							\$	oun	d pre	ssur	e dE	(A)							
1	65	70	75	80	85	90	92	94	96	98	100	102	104	106	108	110	112	114	116	11
2	59	64	69	74	79	84	86	88	90	92	94	96	98	100	102	104	106	108	110	113
3	55	60	65	70	75	80	82	84	86	88	90	92	94	96	98	100	102	104	106	10
5	51	56	61	66	71	76	78	80	82	84	86	88	90	92	94	96	98	100	102	10
10	45	50	55	60	85	70	72	74	78	78	80	82	84	86	88	90	92	94	96	98
20	39	44	49	54	59	64	66	68	70	72	74	78	78	80	82	84	86	88	90	92
30	35	40	45	50	55	60	62	64	66	68	70	72	74	78	78	80	82	84	88	88

Tone o	nd light a	election on	terminal	
ie	N	i.b	Tone and light synchronized	
×	×		pulsing tone / LED Reaking Eght	
×	×	3K)	continuous tone / steady light	
1		1		





Justerbar volym med hjälp av potentiometer, (ej ESK.)



Indication, as also factors like tone type, wind speed, wind direction, humidity, weather conditions etc. do influence the sound pressure dis (A)

| Distance (m) | Sound pressure dis (A) | Sound p



Justerbar volym med hjälp av potentiometer, (ej ESK.)

