



SURFACE MOUNTED SIREN BU1/ PANEL MOUNTED BUZZER BU2/BU3

B100520404

Panel mount buzzer, Ø30mm, 12 V ac/dc, BU2

- High noise level 108 dB
- IP66 embedded cable



PRODUCT DESCRIPTION

BU2/BU3

- Quick and easy installation
- Adjustable noise level at front (approx. 10 dB)
- Pulsating sound

APPLICATION AREA BU1

Surface mounted buzzer with high sound level and high IP-class. With its embedded cable, the siren is easily fitted on the machine without any encapsulation.

APPLICATION AREA BU2/BU3

Small panel mounted buzzer with flat terminal connection. The sound is easily adjusted through a window at the front and the sound can be trimmed up to approx. 10 dB

SPECIFICATIONS

Color House	Black
Diameter	43 mm
IP Class	IP54
Mounting	Panel mount
Nominal current max	0.02 A
Nominal current min	0.02 A
Number of tones	1
Operating Voltage AC / DC Max	16 V
Sound control	Yes
Sound level max	90 dB

Sound level min	80 dB
Supply Voltage	12 V
Supply Voltage AC / DC Min	6 V
Temperature range from	-20 °C
Temperature range to	70 °C
Tone frequency max	3500 Hz
Tone frequency min	2500 Hz
Weight	35 g

