

## R SERIES, MODULAR BEACON Ø95MM

850525405 RDM High Performance LED multifunction beacon, ø95mm, Blue, 24 V ac/dc

- 2 lense heights
- · Modular design easy to mount/service
- Steady, Flashing, Strobe, Rotating and Pulsing light options
- High Performance option
- IP66



## **PRODUCT DESCRIPTION**

The new R Series is the brightest modular LED beacon in its category and is especially designed for maximum signalling effect. Simply pick the required base and choose from a wide range of light modules.

It is available in two lens designs (high/compact). The compact lens is milky-white in colour and its attractive design makes it particularly suitable for indoor use. The high lens is available as a high performance version in addition to the standard performance version.

The R series light modules are available in steady, multicolour and multifunction ranges.


With a Ø95mm Modular beacon and a Ø110mm base, the R Series is a powerful, flexible and robust system. Each light module can be combined with audible base easy. It also offers a simple and safe installation: Pluggable terminal for convenient electrical wiring with plug-in terminal. The standard base comes with cable entry from below through a grommet as well as different hole patterns as knockouts allow easy installation. The universal base offers an additional opening for lateral cable entry/exit and the option for pole mounting (on 25 mm poles) are given. For further mounting types; metal brackets for standard and universal base, metal bracket for acoustic base, design bracket. Combined with its maintenance friendly design it is easy to mount and service.

## SPECIFICATIONS

| Color House  | Black                |
|--------------|----------------------|
| Color Lens   | Blue                 |
| Diameter     | 95 mm                |
| Height       | 124 mm               |
| IK Class     | 8                    |
| IP Class     | IP66                 |
| Light source | High performance LED |
| Light type   | Multi-function       |

| Nominal current         | 1800 mA    |
|-------------------------|------------|
| Nominal Supply Voltage  | 24 V AC/DC |
| Operational Temperature | -30°C 60°C |
| Weight                  | 261 g      |
| Width                   | 110 mm     |
| Voltage Range           | +/-10%     |

|       | Red | Amber<br>[cd] | Yellow<br>[cd] | Green<br>[cd] | Blue<br>[cd] | White<br>[cd] |
|-------|-----|---------------|----------------|---------------|--------------|---------------|
| RDMUP | 118 | 226           | 400            | 127           | 43           | 450           |
| RDMHP | 37  | 116           | 179            | 68            | 14           | 190           |
| RDM   | 25  | 81            | 117            | 40            | 8            | 121           |



| Single Colors | RDC/RDM  | RDM-HP   |
|---------------|----------|----------|
| red           | 24,0 Cd  | 36,0 Cd  |
| amber/orange  | 61,3 Cd  | 101,7 Co |
| yellow        | 101,8 Cd | 168,8 Co |
| green         | 46,4 Cd  | 76,9 Cd  |
| blue          | 8,4 Cd   | 13,9 Cd  |
| white         | 111,0 Cd | 184,0 Co |

