

SIGNAL TOWER Ø 40MM ECO

902001900 ZLL ECO40 STEADY ORANGE >250VAD



- · Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
 - LED steady/LED strobe and LED multi strobe modules
 - Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
 - Piezo buzzer and multi tone siren modules
 - Easy to wire connections
 - Comprehensive range of mounting options including quick mount solutions
 - Plc fit (leakage and inrush current)
 - High ingress protection IP 66 certified to UL type 4/4X/13

SPECIFICATIONS

Color Lens	Orange
Diameter	40 mm
IP Class	IP66

Lamp Socket	Ba15d
Light source	Bulb
Light type	Bulb
Mounting	Bayonet
Number Of Optional Modules	2
Supply Voltage	250 V
Temperature range from	-30 °C
Temperature range to	60 °C
Weight	43 g







