



## SIGNAL TOWER Ø 40MM ECO

902016313

ZDC/GREEN/STEADY LIGHT/LED/230V

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes

- LED steady light

- LED flashing light

- LED strobe light (single flash)

- LED multi strobe light (multi flash)

- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

### SPECIFICATIONS

|            |       |
|------------|-------|
| Color Lens | Green |
| Diameter   | 40 mm |
| IP Class   | IP66  |

|                            |           |
|----------------------------|-----------|
| Light source               | LED       |
| Light type                 | Green LED |
| Mounting                   | Bayonet   |
| Nominal current max        | 0.03 A    |
| Nominal current min        | 0.03 A    |
| Number Of Optional Modules | 2         |
| Operating Voltage AC Max   | 253 V AC  |
| Operating Voltage AC Min   | 207 V AC  |
| Supply Voltage             | 230 V     |
| Temperature range from     | -30 °C    |
| Temperature range to       | 60 °C     |
| Weight                     | 43 g      |

