



SIGNAL TOWER Ø 40MM ECO

902026405

ZDA FLASHING LED GREEN 24VAD

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes

- LED steady light

- LED flashing light

- LED strobe light (single flash)

- LED multi strobe light (multi flash)

- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

SPECIFICATIONS

Color Lens	Green
Diameter	40 mm
Flash Frequency	2 Hz

IP Class	IP66
Light source	LED
Light type	Green LED
Mounting	Bayonet
Nominal current max	0.036 A
Nominal current min	0.028 A
Number Of Optional Modules	2
Operating Voltage AC / DC Max	26.4 V
Supply Voltage	24 V
Supply Voltage AC / DC Min	21.6 V
Temperature range from	-30 °C
Temperature range to	60 °C
Weight	43 g

