

## SIGNAL TOWER Ø 40MM ECO

902042405 ZFF/RED/MULTI STROBE/LED/24VAC/DC



- · Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



## PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
  - LED steady/LED strobe and LED multi strobe modules
  - Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
  - Piezo buzzer and multi tone siren modules
  - Easy to wire connections
  - Comprehensive range of mounting options including quick mount solutions
  - Plc fit (leakage and inrush current)
  - $\bullet$  High ingress protection IP 66 certified to UL type 4/4X/13

## **SPECIFICATIONS**

Color Lens	Red
Diameter	40 mm
Flash Frequency	2.6 Hz

IP Class	IP66
Light source	LED
Light type	Red LED
Mounting	Bayonet
Nominal current max	0.068 A
Nominal current min	0.048 A
Number Of Optional Modules	2
Operating Voltage AC / DC Max	26.4 V
Supply Voltage	24 V
Supply Voltage AC / DC Min	21.6 V
Temperature range from	-30 °C
Temperature range to	60 °C
Weight	43 g







