



## SIGNAL TOWER Ø 60MM ECO

901035313

YDF/BLUE/STROBE LIGHT/LED/230/240 VAC

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

- The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,
- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

### SPECIFICATIONS

|                        |          |
|------------------------|----------|
| <b>Color Lens</b>      | Blue     |
| <b>Diameter</b>        | 60 mm    |
| <b>Flash Frequency</b> | 1.4 Hz   |
| <b>IP Class</b>        | IP66     |
| <b>Light source</b>    | LED      |
| <b>Light type</b>      | Blue LED |
| <b>Mounting</b>        | Bayonet  |

|                            |          |
|----------------------------|----------|
| Nominal current max        | 0.01 A   |
| Nominal current min        | 0.01 A   |
| Number Of Optional Modules | 2        |
| Operating Voltage AC Max   | 253 V AC |
| Operating Voltage AC Min   | 207 V AC |
| Supply Voltage             | 230 V    |
| Temperature range from     | -30 °C   |
| Temperature range to       | 60 °C    |
| Weight                     | 73 g     |

