



## SIGNAL TOWER Ø 60MM ECO

901071405

YFF-HP/AMBER/M-STROBE LIGHT/LED/24V AC

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

- The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,
- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

### SPECIFICATIONS

|                 |            |
|-----------------|------------|
| Color Lens      | Orange     |
| Diameter        | 60 mm      |
| Flash Frequency | 2.6 Hz     |
| IP Class        | IP66       |
| Light source    | LED        |
| Light type      | Orange LED |
| Mounting        | Bayonet    |

|                               |        |
|-------------------------------|--------|
| Nominal current max           | 0.25 A |
| Nominal current min           | 0.19 A |
| Number Of Optional Modules    | 2      |
| Operating Voltage AC / DC Max | 26 V   |
| Supply Voltage                | 24 V   |
| Supply Voltage AC / DC Min    | 18 V   |
| Temperature range from        | -30 °C |
| Temperature range to          | 60 °C  |
| Weight                        | 73 g   |

