



## SIGNAL TOWER Ø 70MM ECO

900017405

XDC LED STEADY YELLOW 24VAD

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

### SPECIFICATIONS

|                            |            |
|----------------------------|------------|
| <b>Color Lens</b>          | Yellow     |
| <b>Diameter</b>            | 70 mm      |
| <b>IP Class</b>            | IP66       |
| <b>Light source</b>        | LED        |
| <b>Light type</b>          | Yellow LED |
| <b>Mounting</b>            | Bayonet    |
| <b>Nominal current max</b> | 0.054 A    |

|                               |         |
|-------------------------------|---------|
| Nominal current min           | 0.049 A |
| Number Of Optional Modules    | 2       |
| Operating Voltage AC / DC Max | 26.4 V  |
| Supply Voltage                | 24 V    |
| Supply Voltage AC / DC Min    | 21.6 V  |
| Temperature range from        | -30 °C  |
| Temperature range to          | 60 °C   |
| Weight                        | 100 g   |









