



SIGNAL TOWER Ø 70MM ECO

900015313

XDC/BLUE/STADY LIGHT/LED/230/240 VAC

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

SPECIFICATIONS

Color Lens	Blue
Diameter	70 mm
IP Class	IP66
Light source	LED
Light type	Blue LED
Mounting	Bayonet
Nominal current max	0.028 A

Nominal current min	0.027 A
Number Of Optional Modules	2
Operating Voltage AC Max	253 V AC
Operating Voltage AC Min	207 V AC
Supply Voltage	230 V
Temperature range from	-30 °C
Temperature range to	60 °C
Weight	100 g









