



SIGNAL TOWER Ø 70MM ECO

900021313

XDA/AMBER/FLASHING LIGHT/LED/230/240 VAC

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

SPECIFICATIONS

| | |
|-----------------|------------|
| Color Lens | Orange |
| Diameter | 70 mm |
| Flash Frequency | 2 Hz |
| IP Class | IP66 |
| Light source | LED |
| Light type | Orange LED |
| Mounting | Bayonet |

| | |
|----------------------------|----------|
| Nominal current max | 0.031 A |
| Nominal current min | 0.03 A |
| Number Of Optional Modules | 2 |
| Operating Voltage AC Max | 253 V AC |
| Operating Voltage AC Min | 207 V AC |
| Supply Voltage | 230 V |
| Temperature range from | -30 °C |
| Temperature range to | 60 °C |
| Weight | 100 g |









