



## I SERIES, PANEL MOUNT BEACON, Ø65, Ø45 AND Ø30MM

802501405

IBL LED STEADY/FLASHING AMBER 24VAC/DC

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range



### PRODUCT DESCRIPTION

The I series offers a high quality, bright, panel mounted beacon. The units can be single or dual colour, have multiple colour and voltage options and in the case of IMM/IMM can be pre-cable with IP67 Protection.

The comprehensive M22 built-in signal device series is available in three sizes Ø 30 mm, Ø 45 mm and Ø 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired.

A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable. Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

### SPECIFICATIONS

<b>Color House</b>	Black
<b>Color Lens</b>	Orange
<b>Diameter</b>	65 mm
<b>Flash Frequency</b>	2 Hz
<b>Height</b>	90 mm
<b>IP Class</b>	IP65
<b>Light source</b>	LED
<b>Light type</b>	Flash
<b>Mounting</b>	Panel mount
<b>Nominal current</b>	60 mA
<b>Nominal Supply Voltage</b>	24 V AC/DC

<b>Operational Temperature</b>	-25°C ... 60°C
<b>Terminal connection</b>	2.5 mm <sup>2</sup>
<b>Weight</b>	75 g

**IBL / IBM / IBS**

La	N	Lb		
X	X		---	FLASHING
X	X	X	—	STEADY

Jumper

