

**I SERIES, PANEL MOUNT BEACON, Ø65,
Ø45 AND Ø30MM**

802514313

ISL/clear/BLIXT/230V AC/IP65

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range

**PRODUCT DESCRIPTION**

The I series offers a high quality, bright, panel mounted beacon. The units can be single or dual colour, have multiple colour and voltage options and in the case of IMM/IMM can be pre-cable with IP67 Protection.

The comprehensive M22 built-in signal device series is available in three sizes Ø 30 mm, Ø 45 mm und Ø 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired.

A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable. Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

SPECIFICATIONS

| | |
|------------------------|-------------|
| Color House | Black |
| Color Lens | Clear |
| Diameter | 65 mm |
| Flash Energy | 1 J |
| Flash Frequency | 1.4 Hz |
| Height | 90 mm |
| IP Class | IP65 |
| Light source | Xenon |
| Light type | Strobe |
| Mounting | Panel mount |

| | |
|-------------------------|---------------------|
| Nominal current | 20 mA |
| Nominal Supply Voltage | 230-240 V AC |
| Operational Temperature | -25°C ... 60°C |
| Terminal connection | 2.5 mm ² |

ISL / ISM / ISS

| La | N | Lb |
|----|---|----|
| X | X | |

