



I SERIES, PANEL MOUNT BEACON, Ø65, Ø45 AND Ø30MM

802515313

Panel mount xenon strobe, Ø65mm, Blue, 230-240 V ac, ISL

- Ø65, Ø45 and Ø30mm Panel mount beacons
- Strobe, Flashing and Steady LED options
- Wide control voltage range



PRODUCT DESCRIPTION

The I series offers a high quality, bright, panel mounted beacon. The units can be single or dual colour, have multiple colour and voltage options and in the case of IMM/IMM can be pre-cable with IP67 Protection.

The comprehensive M22 built-in signal device series is available in three sizes Ø 30 mm, Ø 45 mm und Ø 65 mm. The high luminosity and signal effect is seen all around due to the calotte. The beacon is extremely durable and vibration-resistant, with a high degree of protection of IP65 and IP67 for prewired models. The I Series range can come with a demountable plug in terminal or individually prewired.

A complete range of LED steady/flashing/strobe and multi colour models for versatile applications in the industry, enclosures, etc. It is maintenance free, offers a low current consumption, long life time, shock and vibration-proof. Multi colour models are also available in 6 LED colours individually selectable. Housing and lenses made of impact resistant polycarbonate, housing colour black or grey.

SPECIFICATIONS

Color House	Black
Color Lens	Blue
Diameter	65 mm
Flash Energy	1 J
Flash Frequency	1.4 Hz
Height	90 mm
IP Class	IP65
Light source	Xenon
Light type	Strobe
Mounting	Panel mount

Nominal current	20 mA
Nominal Supply Voltage	230-240 V AC
Operational Temperature	-25°C ... 60°C
Terminal connection	2.5 mm ²

ISL / ISM / ISS

La	N	Lb
X	X	

