



## **SURFACE MOUNTED SIREN BU1/ PANEL MOUNTED BUZZER BU2/BU3**

B100520405

BU2 PULSATING BUZZER 24VAC/DC

- High noise level 108 dB
- IP66 embedded cable



### **PRODUCT DESCRIPTION**

#### **BU2/BU3**

- Quick and easy installation
- Adjustable noise level at front (approx. 10 dB )
- Pulsating sound

#### **APPLICATION AREA BU1**

Surface mounted buzzer with high sound level and high IP-class. With its embedded cable, the siren is easily fitted on the machine without any encapsulation.

#### **APPLICATION AREA BU2/BU3**

Small panel mounted buzzer with flat terminal connection. The sound is easily adjusted through a window at the front and the sound can be trimmed up to approx. 10 dB

### **SPECIFICATIONS**

<b>Color House</b>	Black
<b>Diameter</b>	43 mm
<b>IP Class</b>	IP54
<b>Mounting</b>	Panel mount
<b>Nominal current max</b>	0.03 A
<b>Nominal current min</b>	0.03 A
<b>Number of tones</b>	1
<b>Operating Voltage AC / DC Max</b>	28 V
<b>Sound control</b>	Yes
<b>Sound level max</b>	90 dB

Sound level min	80 dB
Supply Voltage	24 V
Supply Voltage AC / DC Min	12 V
Temperature range from	-20 °C
Temperature range to	70 °C
Tone frequency max	3500 Hz
Tone frequency min	2500 Hz
Weight	35 g

