



## SURFACE MOUNTED SIREN BU1/ PANEL MOUNTED BUZZER BU2/BU3

B100520313

BU3 PULSATING BUZZER 230VAC

- High noise level 108 dB
- IP66 embedded cable



### PRODUCT DESCRIPTION

#### BU2/BU3

- Quick and easy installation
- Adjustable noise level at front (approx. 10 dB )
- Pulsating sound

### APPLICATION AREA BU1

Surface mounted buzzer with high sound level and high IP-class. With its embedded cable, the siren is easily fitted on the machine without any encapsulation.

### APPLICATION AREA BU2/BU3

Small panel mounted buzzer with flat terminal connection. The sound is easily adjusted through a window at the front and the sound can be trimmed up to approx. 10 dB

### SPECIFICATIONS

Color House	Black
Diameter	43 mm
IP Class	IP54
Mounting	Panel mount
Nominal current max	0.02 A
Nominal current min	0.02 A
Number of tones	1
Operating Voltage AC Max	240 V AC
Operating Voltage AC Min	180 V AC
Sound control	Yes

Sound level max	90 dB
Sound level min	80 dB
Temperature range from	-20 °C
Temperature range to	70 °C
Tone frequency max	3500 Hz
Tone frequency min	2500 Hz
Weight	35 g

