

**T SERIES, MODULAR BEACON, Ø75MM**

859506405

TDC GREEN LED STEADY/FLASHING 24VAC/DC

- Ø75mm Modular beacon
- Steady, flashing and Multi-strobe light options
- Wide control voltage range

**PRODUCT DESCRIPTION**

AUER's T Series range begins with a Ø 75 mm large comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a steady beacon option with BA15d socket for 7 W incandescent bulb, the T Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13 (excluding TNL and TMW+TVS).

There are also optionally available protective vents for pressure balance in harsh weather conditions (humidity, high temperature fluctuations, etc.) for TMW, TMF, TNL. A comprehensive range of selectable mounting options, and an Ingress protection of IP66.

**SPECIFICATIONS**

<b>Color Lens</b>	Green
<b>Diameter</b>	75 mm
<b>Flash Frequency</b>	2 Hz
<b>Height</b>	75 mm
<b>IK Class</b>	8
<b>IP Class</b>	IP66
<b>Light source</b>	LED
<b>Light type</b>	Flash, Steady
<b>Mounting</b>	Bayonet
<b>Nominal current</b>	220 mA

Nominal Supply Voltage 24 V AC/DC

Operational Temperature -30°C ... 60°C

Terminal connection 2.5 mm<sup>2</sup>

Weight 86 g

