



T SERIES, MODULAR BEACON, Ø75MM

859505310

LED Steady/flashing, Ø75mm, Blue, 110-120 V ac,
TDC

- Ø75mm Modular beacon
- Steady, flashing and Multi-strobe light options
- Wide control voltage range



PRODUCT DESCRIPTION

AUER's T Series range begins with a Ø 75 mm large comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a steady beacon option with BA15d socket for 7 W incandescent bulb, the T Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13 (excluding TNL and TMW+TVS).

There are also optionally available protective vents for pressure balance in harsh weather conditions (humidity, high temperature fluctuations, etc.) for TMW, TMF, TNL. A comprehensive range of selectable mounting options, and an Ingress protection of IP66.

SPECIFICATIONS

| | |
|-----------------|---------------|
| Color Lens | Blue |
| Diameter | 75 mm |
| Flash Frequency | 2 Hz |
| Height | 75 mm |
| IK Class | 8 |
| IP Class | IP66 |
| Light source | LED |
| Light type | Flash, Steady |
| Mounting | Bayonet |
| Nominal current | 72 mA |

