

**T SERIES, MODULAR BEACON, Ø75MM**

859507313

TDC YELLOW LED STEADY/FLASHING 230VAC

- Ø75mm Modular beacon
- Steady, flashing and Multi-strobe light options
- Wide control voltage range

**PRODUCT DESCRIPTION**

AUERs T Series range begins with a Ø 75 mm large comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a steady beacon option with BA15d socket for 7 W incandescent bulb, the T Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13 (excluding TNL and TMW+TVS).

There are also optionally available protective vents for pressure balance in harsh weather conditions (humidity, high temperature fluctuations, etc.) for TMW, TMF, TNL. A comprehensive range of selectable mounting options, and an Ingress protection of IP66.

**SPECIFICATIONS**

|                        |               |
|------------------------|---------------|
| <b>Color Lens</b>      | Yellow        |
| <b>Diameter</b>        | 75 mm         |
| <b>Flash Frequency</b> | 2 Hz          |
| <b>Height</b>          | 75 mm         |
| <b>IK Class</b>        | 8             |
| <b>IP Class</b>        | IP66          |
| <b>Light source</b>    | LED           |
| <b>Light type</b>      | Flash, Steady |
| <b>Mounting</b>        | Bayonet       |
| <b>Nominal current</b> | 66 mA         |

|                         |                     |
|-------------------------|---------------------|
| Nominal Supply Voltage  | 230-240 V AC        |
| Operational Temperature | -30°C ... 60°C      |
| Terminal connection     | 2.5 mm <sup>2</sup> |
| Weight                  | 86 g                |

